

405nm 15mW~20mW SM Pigtailed Laser Diode Module With Coaxial Package

405nm 15mW Single Mode Fiber Coupled Diode Laser Module | Violet LD Module With SMF

WSLP-405-015m-4

Wavespectrum Laser Group


www.wavespectrum-laser.com

405nm Pigtailed Diode Laser	15mW/SMF	en.wavespectrum-laser.com.cn
-----------------------------	----------	------------------------------


PARAMETER	SYMBOL	VALUE	UNIT
Reverse Voltage	V_r	2.0	V
Operating Temperature	T_{op}	-10 ~ +70	°C
Storage Temperature	T_{stg}	-40 ~ +85	°C
Lead soldering temperature (10 sec.)	T_{is}	260	°C
Features: 405nm 3um SM Fiber - Coaxial or B82 Package			
Applications: - Medical Laser Treatment - Printing - Others			
Specifications	WSLP-405-015m-4		
	Min	Type	Max
Center Wavelength@25°C	±5nm	405nm	±10nm
Spectral Width (FWHM)	----	2.0nm	----
Output Power	----	15mW	----
Fiber Type	UV Single Mode Fiber		
Fiber Core	3um		
Recommend Operating Temperature	25°C		
Monitor Current	----	----	----
PD Reverse Voltage	----	----	----
Fiber Connector	FC/SC/SMA905		
Fiber Length	----	80cm	100cm
Threshold Current	----	35mA	70mA
Operating Current	----	90mA	110mA
Operating Voltage	----	5.0V	6.0V
Package Style	Coaxial or B82		




Coaxial Package View: (Part Number: WSLP-405-015m-4)



B82 Package View: (Part Number: WSLP-405-015m-4-B)



PIN Bottom View:



1	LD(+)
2	GND
3	LD(-)



Electrically shorten LD module and store in non-extreme conditions.

Suggest using the constant current power supply.

