

515nm~520nm 20mW Single Mode Fiber Coupled Diode Laser With Photodiode (PD) | Built-in TEC cooler
520nm 20mW~30mW |HHL Package| SM Fiber| Green Diode Laser | Built-in TEC Cooling | High Stability
WSLX-520-020m-4-H8-T-PD **Wavespectrum Laser Group** **www.wavespectrum-laser.com**

PARAMETER	SYMBOL	VALUE	UNIT
Reverse Voltage	V_r	2.0	V
Operating Temperature	T_{op}	-10~+60	°C
Storage Temperature	T_{stg}	-40~+80	°C
Lead soldering temperature (5 sec.)	T_{is}	250	°C

Features:

- 520nm
- 3um SM Fiber
- Built-in TEC Cooling
- Built-in Photodiode

Applications:

- Medical Laser Treatment
- Others





Specifications

WSLX-520-020m-4-H8-T-PD

	Min.	Type	Max.
Center Wavelength@25°C	±5nm	520nm	±10nm
Spectral Width (FWHM)	----	2nm	----
Output Power	----	20mW	----
Recommend Operating Temperature	25 °C		
Threshold Current (Typ.)	----	45mA	75mA
Operating Current (Typ.)	----	200mA	220mA
Operating Voltage	----	7.5V	8.0V
Monitor Current	----	100uA	----
TEC Max Current	1.5A		
TEC Max Voltage	4.0V		
Thermistor	10K		
Fiber Type	Single Mode Fiber		
Fiber Core	3um		
Fiber Length	>80cm		
Connector Type	FC/SC/SMA905		
Package Style	8-PIN		



8-Pin Package View:

Pin Out:


PIN	FUNCTION	PIN	FUNCTION
1	RT	5	PD(+)
2	LD(-)	6	NC
3	LD(+)&PD(-)	7	TEC(-)
4	RT	8	TEC(+)

Wavespectrum offer Customized 520nm Fiber Coupled LD.

- Customized Output Power
- Customized Fiber Core
- Dual-Wavelength or Tri-Wavelength Module Optional
(such as 2W@520nm+ 10W@980nm)

Contact us with info@wavespectrum-laser.com

Electrically shorten LD module and store in non-extreme conditions.

Suggest using the constant current power supply.



Wavespectrum Laser Group
www.wavespectrum-laser.com
sales@wavespectrum-laser.com

