

450nm~455nm 4W HHL Package Fiber Coupled Diode Laser With MM Fiber | Blue Laser Diode
455nm 4W | 9-Pin HHL Package | 200um, 400um fiber optional |TEC Cooling | Built-in PD
WSLX-455-004-200M-H9-T-PD
Wavespectrum Laser Group
www.wavespectrum-laser.com

PARAMETER	SYMBOL	VALUE	UNIT
MAX Reverse Current	I_r	80	mA
Operating Temperature	T_{op}	+10 ~ +30	°C
Storage Temperature	T_{stg}	-40 ~ +85	°C
Lead soldering temperature (10 sec.)	T_{is}	260	°C

Features:

- 455nm
- 4W Output Power
- Built-in TEC Cooling
- Built-in PD
- High Stability

Applications:


- Medical Laser Treatment
- Others


Specifications
WSLX-455-004-200M-H9-T-PD

	Min.	Type	Max.
Center Wavelength@25°C	455nm±10nm		
Spectral Width (FWHM)	----	3nm	----
Output Power	----	4W	----
Recommend Operating Temperature	25 °C		
Threshold Current (Typ.)	----	0.2A	0.6A
Operating Current (Typ.)	----	3.2A	3.5A
Operating Voltage		4.5V	5.5V
TEC Max Current	6A		
TEC Max Voltage	9.8V		
Thermistor	10K		
Fiber Type	Multi-mode Fiber		
Fiber Core	200um (400um optional)		
Fiber Length	>80cm		
Connector Type	SMA905/FC		



9-PIN HHL Package View



PIN	FUNCTION
1	TEC (-)
2	-
3	CASE
4	LD (+)
5	THERM
6	THERM
7	LD (-)
8	PD (P)
9	PD (N)
10	TEC (+)

Wavespectrum offer **Customized** 455nm Fiber Coupled LD.

- Customized Output Power
- Customized Fiber Core
- Dual-Wavelength or Tri-Wavelength Module Optional
(such as 500mw@455nm+10W@980nm)

Contact us with info@wavespectrum-laser.com

Electrically shorten LD module and store in non-extreme conditions.

Suggest using the constant current power supply.



Wavespectrum Laser Group
www.wavespectrum-laser.com
sales@wavespectrum-laser.com

