

505nm~510nm 50mW Multi-mode Fiber Coupled Diode Laser With TEC cooler

505nm 50mW | 8-Pin Package | Green Diode Laser | Built-in TEC Cooling | High Stability

WSLX-505-050m-M-H8-T


Wavespectrum Laser Group

en.wavespectrum-laser.com.cn


PARAMETER	SYMBOL	VALUE	UNIT
Reverse Voltage	V_r	2.0	V
Operating Temperature	T_{op}	+10 ~ +30	°C
Storage Temperature	T_{stg}	-20 ~ +80	°C
Lead soldering temperature (10 sec.)	T_{is}	260	°C
Features: 505nm Multi-mode Fiber Built-in TEC Cooling Built-in PD Optional			
Applications: Medical Laser Treatment Others			
Specifications	WSLX-505-050m-M-H8-T		
	Min.	Type	Max.
Center Wavelength@25°C	505nm±10nm		
Spectral Width (FWHM)	----	2nm	----
Output Power	----	50mW	----
Recommend Operating Temperature	25 °C		
Threshold Current (Typ.)	----	55mA	95mA
Operating Current (Typ.)	----	220mA	240mA
Operating Voltage	----	7.5V	8.0V
Monitor Current	----	----	----
TEC Max Current	1.3A		
TEC Max Voltage	4.0V		
Thermistor	10K		
Fiber Core Diameter	105um		
Fiber Numerical Aperture	0.22		
Fiber Length	>80cm		
Connector Type	FC/SC/SMA905		
Package Style	8-PIN		



8-Pin Package View:



Pin Out:



PIN	FUNCTION	PIN	FUNCTION
1	RT	5	NC
2	LD (-)	6	NC
3	LD (+)	7	TEC (-)
4	RT	8	TEC (+)

Wavespectrum offer Customized 505nm Fiber Coupled LD.

- Customized Output Power
- Customized Fiber Core
- Dual-Wavelength or Tri-Wavelength Module Optional
(such as 50mW@505nm + 10W@980nm)

Contact us with info@wavespectrum-laser.com

Electrically shorten LD module and store in non-extreme conditions.

Suggest using the constant current power supply.



Wavespectrum Laser Group
www.wavespectrum-laser.com
sales@wavespectrum-laser.com

