

515nm~520nm 30mW Multi-mode Fiber Coupled Diode Laser With Photodiode (PD) | Built-in TEC cooler

520nm 30mW | 8-Pin Package| Green Diode Laser | Built-in TEC Cooling | High Stability

WSLX-520-030m-M-H8-T-PD

Wavespectrum Laser Group

en.wavespectrum-laser.com.cn

PARAMETER	SYMBOL	VALUE	UNIT
Reverse Voltage	V_r	2.0	V
Operating Temperature	T_{op}	+10 ~ +30	°C
Storage Temperature	T_{stg}	-20 ~ +80	°C
Lead soldering temperature (10 sec.)	T_{is}	260	°C

Features:

- 520nm
- Multi-mode Fiber
- Built-in TEC Cooling
- Built-in Photodiode

Applications:

- Medical Laser Treatment
- Others



Specifications

WSLX-520-030m-M-H8-T-PD

	Min.	Type	Max.
Center Wavelength@25°C	520nm±10nm		
Spectral Width (FWHM)	----	2nm	----
Output Power	----	30mW	----
Recommend Operating Temperature	25 °C		
Threshold Current (Typ.)	----	40mA	80mA
Operating Current (Typ.)	----	160mA	180mA
Operating Voltage	----	7.0V	8.0V
Monitor Current	----	100uA	----
TEC Max Current	1.3A		
TEC Max Voltage	4.0V		
Thermistor	10K		
Fiber Core Diameter	105um		
Fiber Numerical Aperture	0.22		
Fiber Length	>80cm		
Connector Type	FC/SC/SMA905		
Package Style	8-PIN		


Wavespectrum Laser Group

www.wavespectrum-laser.com


sales@wavespectrum-laser.com



8-Pin Package View:



Pin Out:



PIN	FUNCTION	PIN	FUNCTION
1	RT	5	PD (+)
2	LD (-)	6	NC
3	LD (+) & PD (-)	7	TEC (-)
4	RT	8	TEC (+)

Wavespectrum offer Customized 520nm Fiber Coupled LD.

- Customized Output Power
- Customized Fiber Core
- Dual-Wavelength or Tri-Wavelength Module Optional
(such as 2W@520nm+10W@980nm)

Contact us with info@wavespectrum-laser.com

Electrically shorten LD module and store in non-extreme conditions.

Suggest using the constant current power supply.



Wavespectrum Laser Group
www.wavespectrum-laser.com
sales@wavespectrum-laser.com

