

660nm~670nm 10W High Power Fiber Coupled Laser Diode Module

670nm 10W| 400um Fiber Core| High Power LD | Built-in Thermistor

WSLX-670-010-400M-J21

Wavespectrum Laser Group

en.wavespectrum-laser.com.cn

PARAMETER	SYMBOL	VALUE	UNIT
Reverse Voltage	V_r	2.0	V
Operating Temperature	T_{op}	+10 ~ +30	°C
Storage Temperature	T_{stg}	-20 ~ +80	°C
Lead soldering temperature (10 sec.)	T_{is}	260	°C

Features: 670nm 10W Output Power 400um Fiber Core - Built-in Thermistor - Aiming Light Optional	
Applications: - Medical Laser Treatment - Others	

Specifications	WSLX-670-010-400M-J21		
	Min.	Type	Max.
Center Wavelength@25°C	670nm±10nm		
Spectral Width (FWHM)	----	6nm	----
Output Power	----	10W	----
Temperature Coefficient of Wavelength	----	0.2nm / °C	----
Threshold Current (Typ.)	----	0.5A	1.2A
Operating Current (Typ.)	----	1.8A	2.0A
Operating Voltage	----	22V	26V
Recommended Case Temperature	25°C		
Thermistor	10K		
Photodiode	Optional		
Fiber Core Diameter	400um		
Fiber Numerical Aperture	0.22		
Fiber Length	>80cm		
Connector Type	SMA905/ST/FC		
Package Style	J21A Package		
Aiming Beam	Optional		



